



- Fastest data transfers currently available
- Huge storage capacity(20/30/40/60/80GB)
- Pre-formatted and ready to Plug-n-Go
- Supports FireWire + USB2
- Bus power capability on supported systems
- Great for multimedia/data transfer
- Hot-swap capability/Plug & Play
- 3 Year Limited Warrant

Want the ultimate in convenience and file transfer speed? It's time to step up to Fire-n-Ice To-Go dual port external FireWire drives from Think Storage. Whether you are looking for a bus powered solution for multimedia projects, image editing, backup, or just need increased capacity, Fire-n-Ice drives are a perfect solution. Our drives are small enough to fit in a shirt pocket, yet can store up to 80GB. These drives feature the fastest FireWire

bridge available "Oxford 911" and use internal drives that are built for speed and built to last. Because Fire-n-Ice To-Go drives don't require external power, they can be used on planes, boats, trains or wherever your travels may take you.

Specifications		Features & Benefits
Bus Interface	FireWire (IEEE1394/iLink Compliant), USB 2.0	<ul style="list-style-type: none"> • Ideal for transporting and backing up large amounts of data • Lightweight and pocket sized for ultimate portability • 6-pin IEEE-1394 port + USB2 • Supports Mac OS 8.6 and above, Windows 98SE/2000/ME/XP • Plug & Play/Hot Plug & Unplug
Capacity	40, 60, 80 Gigabyte	
Max Data Transfer Rate	235,216 (Mbits/sec) 20GB, 30GB & 40GB - 4200 RPM 60GB - 5400 RPM	
System Requirements	Macintosh with FireWire Interface and OS 8.6 and above or PC with FireWire or USB2 With Window 98SE, Window 2000, Window ME or other OS with FireWire Support.	
Total Shipping Weight:	Less than 1.5lbs/.8kgs including Power Transformer	
Weight:	10.23 Ounces	
Power Supply	110v-240v auto switchable power from FireWire bus power or external DC adapter	
FireWire bus power input:	DC 8 to 30V, 1A	
DC adapter power input:	DC 5V, 1A	
External Case Dimensions:	3.23" (W) x 5.67" (D) x 1.14" (H)	
Operating Environment Temperature:	(Operating) 5deg;C - 55deg;C (41deg;F - 131deg;F) (Non-operating) -40deg;C - 65deg;C (-40deg;F - 149deg;F)	
Relative humidity:	(Operating) 8% - 90% RH (Non-condensing) (Non-operating) 5% - 95% RH (Non-condensing)	
Shock:	800 G/2 mS	
Vibration:	3.01G(5-500Hz)	
MTBF:	More than 300,000 power-on hours	
Warranty:	3 year limited warranty	

*Note: Although the Fire-n-Ice Dual Port drive is compatible with older USB technology, USB 1.1 only supports up to 12Mb/sec or 1.5MB/ sec sustained transfer rates. If you plan on using a USB port, Think recommends that you upgrade using the ThinkCP™ Technologies PCI/USB2 or PCMCIA/ USB2 interface for USB speeds up to 40X faster than USB 1.1.



For more information on ThinkCP™ please call toll free (800) 726-2477 or visit us at www.ThinkCP.com



Rev. 10/03

Copyright ©2006 H. Co. Computer Products. All Rights Reserved. ThinkCP™ and H. Co. Computer Products™ are trademarks or registered trademarks of H. Co. Computer Products, Inc. For additional information regarding our trademarks, please visit trademark info at <http://www.ThinkCP.com>. This list is not intended to be an all-inclusive or comprehensive list of all H. Co. Computer Products trademarks and/or intellectual properties. Other product names used herein are for identification purposes only and may be the respective property or trademarks of other companies.

ThinkCP™ Technologies • 16812 Hale Avenue • Irvine, California 92606 • Toll Free: (800) 726-2477
Phone: (949) 833-3222 • Fax: (949) 833-3389 • www.ThinkCP.com • info@thinkcp.com

