

Think Dual Port External FireWire/Hi-Speed USB2 Drive



- Proven Quality & Performance from the Makers of The Original Award Winning "Fire-n-Ice" FireWire Drives
- Includes both FireWire IEEE 1394 & USB2 Ports for Flexibility
- Huge Storage Capacities (40/60/80/120/160/200/250/300GB)
- Hot-Swappable And Plug & Play Ready
- 3 Year Limited Warranty

Want the ultimate in file transfer quality, speed, ease & flexibility? It's time to upgrade to the latest Fire-n-Ice Dual Port FireWire/USB2 drives from Think Computer Products. The latest Fire-n-Ice drives feature a cool design, a space-saving footprint and they're still among the industry's fastest external hard drive storage solutions! Fire-n-Ice drives combine the Oxford 911 bridge, 7200 RPM drives with 2Mb cache to create the perfect solution for professionals and novices alike. It's a simple way to extend your systems storage capacity. You can even daisy-chain Fire-n-Ice drives for easy scalability without sacrificing data speed or integrity.

Specifications		Features & Benefits	
Bus Interface	FireWire (IEEE1394/Link Compliant); USB 2.0	<ul style="list-style-type: none"> • Ultra fast read/write speeds perfect for video/image editing and other large file applications • Ideal for transporting and backing up large amounts of data • Lightweight and portable size • FireWire IEEE 1394 & USB2 support • USB2 backward compatible with USB1.1* • Supports Windows SE/2000/ME/XP & Mac OS 8.6 or higher <p><small>*Note: Although the Fire-n-Ice Dual Port drive is compatible with older USB technology, USB 1.1 only supports up to 12Mb/sec or 1.5MB/sec sustained transfer rates. If you plan on using a USB port, Think recommends that you upgrade using the Think Computer Products PCI/USB2 or PCMCIA/USB2 interface for USB speeds up to 40X faster than USB 1.1.</small></p>	 
Capacity	40, 60, 80, 120, 160, 200, 250, 300 Gigabytes		
Max Data Transfer Rate	FireWire 400Mbps; USB2 480Mb/sec		
Sustained Transfer Rates	FireWire 40MB/sec; USB2 34MB/sec		
System Requirements	Windows 98SE/2000/ME/XP, Mac OS 8.6 or higher & either FireWire or USB Port*		
Total Shipping Weight:	Less than 3.5 pounds (7.7kg)		
Power Supply	110v-240v auto switching; external power adapter.		
FireWire bus power input:	DC 8 to 30V, 1A		
DC adapter power input:	DC 5V, 1A		
External Case Dimensions:	1.5 in (W) x 9 in (D) x 5.5 in (H)		
Operating Environment Temperature:	(Operating) 5deg:C - 55deg:C (41deg:F - 131deg:F) (Non-operating) -40deg:C - 65deg:C (-40deg:F - 149deg:F)		
Relative humidity:	(Operating) 8% - 90% RH (Non-condensing) (Non-operating) 5% - 95% RH (Non-condensing)		
Shock:	(Operating) 65G 2mS, (Non-operating) 175G 2mS		
Vibration:	(Operating) 1.0G (5 - 300Hz), (Non-operating) 5.0G (5-500Hz)		
MTBF:	More than 300,000 power-on hours		
Warranty:	3 year limited warranty		
Standard Mechanism:	7200RPM ATA/100 2MB cache buffer		

For more information on ThinkCP™ please call toll free (800) 726-2477 or visit us at www.ThinkCP.com

Copyright ©2006 H. Co. Computer Products. All Rights Reserved. ThinkCP™ and H. Co. Computer Products™ are trademarks or registered trademarks of H. Co. Computer Products, Inc. For additional information regarding our trademarks, please visit trademark info at <http://www.ThinkCP.com>. This list is not intended to be an all-inclusive or comprehensive list of all H. Co. Computer Products trademarks and/or intellectual properties. Other product names used herein are for identification purposes only and may be the respective property or trademarks of other companies.

ThinkCP™ Technologies • 16812 Hale Avenue • Irvine, California 92606 • Toll Free: (800) 726-2477
Phone: (949) 833-3222 • Fax: (949) 833-3389 • www.ThinkCP.com • info@thinkcp.com



Rev. 2/04

